



ATLANTIC CALCIUM CHASSIS GREASE – MP 3

(CALCIUM BASE GREASE, AVAILABLE IN NLGI 2, 3)

DESCRIPTION & APPLICATIONS

ATLANTIC CALCIUM CHASSIS GREASE provides excellent resistance to moisture and water washout. It is especially well-suited for applications in damp or wet environments. It is primarily used in low to moderate temperature and low-speed applications where water exposure is a concern. Common areas of use include automotive chassis lubrication (such as suspension parts and steering linkages), water pump bearings in older vehicles, and various types of agricultural, marine, and industrial machinery. It's also widely used in construction and mining equipment exposed to outdoor conditions.

PERFORMANCE FEATURES AND BENEFITS

- Excellent water resistance
- Good mechanical stability
- Excellent against rust and corrosion, contributing to extended equipment life.
- Its strong adhesive properties allow it to cling well to metal surfaces, minimizing grease loss during operation.

TYPICAL CHARACTERISTICS

PRODUCT CODE:	AGL-G-250014
Thickener Type	Calcium
NLGI Classification	3
Texture	Smooth
Color, Visual	Amber
Dropping Point °C, ASTM D 566	95-105
Worked Penetration @25°C 60 strokes, ASTM D 217	220-250
Wheel Bearing leakage after 6hrs @ 110°C gms, ASTM D 1263	<2
Water washout resistance %wt, ASTM D 1264	<5
Copper Strip Corrosion for 24hrs @100°C, ASTM D 4048	1b

Packing: 400g, 500g, 1kg, 3.5kg, 5kg, 15kg, 18kg, 180kg

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

ATL/PDS/G/014/01*, 04.01.24, Page 1/1

* supersedes all previous versions