



ATLANTIC WIRE ROPE SAFE GREASE 00

(WIRE ROPE GREASE)

DESCRIPTION & APPLICATIONS

ATLANTIC WIRE ROPE SAFE GREASE 00 is a heavy-duty extreme pressure grease, pre-eminently designed for the lubrication of industrial bearings working under high temperatures and high loads in the steel industry. It is also suitable as EP multi-purpose grease, in various other industrial applications where water is in frequent contact with the grease.

Always avoid contamination of the grease by dust and/or dirt when applying.

PERFORMANCE FEATURES AND BENEFITS

- Multi-purpose
- Excellent thermal and mechanical stability
- Water resistant
- Long service life.
- No harmful substances
- High extreme pressure and anti-wear properties.
- Good pumpability.
- Extraordinary resistance to wash-off by water
- Excellent anti-oxidation and anti-corrosion properties

TYPICAL CHARACTERISTICS

PRODUCT CODE:	AGL-G-250023
Thickener Type	Lithium-Complex + Molybdenum Disulphide
NLGI Classification	00
Texture	Smooth
Color, Visual	Grey/Black
Dropping Point, °C, ASTM D566	240
Worked Penetration @25°C 60 strokes, ASTM D217	400-430
Operating temperature range, °C	-25 to 180
Kinematic viscosity of the base oil at 40°C, mm ² /s, ASTM D 445	420
Four ball weld load, kgf, ASTM D 2596	300
Anti-rust performance SKF- EMCOR, DIN 51 802, rating	0-0

Packing: 400g, 500g, 1kg, 3.5kg, 5kg, 15kg, 18kg, 180kg

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

ATL/PDS/G/023/01*, 04.01.24, Page 1/1

* supersedes all previous versions