



ATLANTIC FRENO BRAKE FLUID DOT 4 PLUS

High Performance Glycol Ether Based Brake Fluid

DESCRIPTION

ATLANTIC FRENO Brake Fluid DOT 4 Plus has been specially designed for use in heavy-duty brake systems of vehicles that require a DOT 4 synthetic brake fluid. The product is particularly recommended for brake systems with ABS. ATLANTIC FRENO Brake Fluid DOT 4 Plus Brake Fluid can be mixed with all synthetic brake fluids of the same grade.

APPLICATIONS

ATLANTIC FRENO Brake Fluid DOT 4 Plus is designed to excel within the extreme demands made on a race vehicle or by high performance drivers and exceeds all DOT4 standards. It is compatible with and will mix well with most DOT3, DOT4 or DOT 5.1 fluids.

PERFORMANCE FEATURES AND BENEFITS

- High dry boiling point
- High wet boiling point
- High lubrication power
- Exceptional low viscosity at low temperature
- Miscibility with all brake fluids of the same specification

RECOMMENDATIONS / SPECIFICATIONS

ISO 4925, Class 6, FMVSS 116, DOT 4, SAE J1704, MB 276.40.

Meets the quality requirements of European Manufacturers

TYPICAL TECHNICAL PROPERTIES

PRODUCT CODE	ASP-BF-25004
Density at 20°C, g/ml, ASTM D4052	1.069
Kinematic Viscosity at -40°C, mm²/s, ASTM D445	1300
Kinematic Viscosity at 100°C, mm²/s, ASTM D445	2.16
Dry ERBP (FMVSS No. 116) S.11, °C (min.)	265
pH (FMVSS No. 116) S.14	7.49
Corrosion Test @ 100°C for 120hrs	passes test

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

STORAGE STABILITY

Storage time is up to three years in sealed, metal, bulk containers. Protection should be provided to prevent any moisture contamination. Moisture contamination will result in a 5-10°C boiling point drop for each 0.1% of water absorbed.

Packing: 250 ml, 244 ml, 500 ml, 1L, 200L, 205L, 208L, 210L

ATL/PDS/ASP/001b-12521xASP/01*, 01.06.25, Page 1/1

* supersedes all previous versions