



ATLANTIC ANTIFREEZE COOLANT - GREEN

CONVENTIONAL ANTIFREEZE COOLANT



DESCRIPTION

ATLANTIC ANTIFREEZE COOLANT - GREEN is a conventional (green), ethylene glycol-based antifreeze for use in older automotive and light duty gasoline/diesel applications. ATLANTIC Antifreeze + Coolant provides maximum protection from freezing to -84°F and boil-over to +276°F. Protects all cooling system metals, including aluminum, against damaging rust and corrosion when used as recommended.

APPLICATIONS

ATLANTIC ANTIFREEZE COOLANT - GREEN is engineered for use in older passenger cars, and light duty trucks

PERFORMANCE FEATURES AND BENEFITS

- Maximum Freeze-Up Protection To -84°F Boil-Over Protection To +276°F*
- Provides Year-Round Protection against Damaging Rust and Corrosion
- Compatible with All Conventional (Green) Antifreeze + Coolants
- Meets or exceeds ASTM D3306 and D4985 specifications

TYPICAL FREEZE/BOILOVER PROTECTION MIXING CHART

(Using a 103.4 kPa pressure cap)

Mixing Ratio		Freezing Point	Boilover
Antifreeze concentrate (%)	Demineralized water (%)	Protection (°C)	Protection (°C)
50	50	-36	+109
60	40	-52	+132
70	30	-64	+135

RECOMMENDATIONS / SPECIFICATIONS

Engineered for use in older passenger cars, and light duty trucks including:

Chrysler: All Pre-2000, Ford: All Pre-2002, GM: All Pre-1995, All makes and models: All Pre-1989

Also recommended for use where the following are cited:

Chrysler/FCA MS-7170, Ford ESE-M97B44-A, General Motors GM 1899M, GM 1825M, TMC RP 302C, SAE J814

TYPICAL TECHNICAL PROPERTIES

PRODUCT CODE:	ASP-COOL-25005		
CHARACTERISTIC	CONCENTRATE	50/50	ASTM D3306 LIMITS
Appearance, visual	Green	Green	-
Specific gravity, ASTM D1122	1.120-1.130	1.070-1.080	7.5-11.0
pH, (50% vol), ASTM D1287	10.5	10.5	1.110-1.145/1.065
Boiling point, °C (°F), ASTM D1120	163(325)	109 (229)	163 (325)/108(226) Min
Freezing point, °C (°F), ASTM D1177	---	-37.9 (-36.2)	-36.4 (-34) Max
Effect on Automotive Finish, ASTM D1882	No Effect	No Effect	No Effect
Total water, mass %, ASTM D1123	<5	50	Report
Ash content, mass %, ASTM D1119	<5	<2.5	5 Max*
Chloride, ppm, ASTM 3634	<25	<25	25 Max

*concentrate only

Packing: 1L, 4L, 5L, 20L, 200L, Bulk

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

ATL/PDS/ASP-14G/02*, 01.06.25, Page 1/1

* supersedes all previous versions