



ATLANTIC FORK OIL 10W

Premium Motorcycle Suspension Oil

DESCRIPTION

ATLANTIC FORK OILS 10W is highly stable suspension oils, recommended for use in motorcycle forks and shocks for road, off road and competition use. They are blended from highly refined base stocks and contain selected additives to provide protection against wear, corrosion and to minimize the effect of foam or air entrainment in the fork.

APPLICATIONS

ATLANTIC FORK OILS are carefully designed to meet the varying viscosity requirements of motorcycle forks, dampers and suspension.

PERFORMANCE FEATURES AND BENEFITS

- Prolongs seal life by resisting premature hardening and glazing, ensuring efficient fork operation.
- Consistent fork operation over wide temperature range.
- Can be mixed with other Atlantic Fork Oil grades to obtain intermediate grades.
- Helps to minimize rust and corrosion.
- Suppresses foam to ensure efficient damping operation.
- Long life

TYPICAL TECHNICAL PROPERTIES

PRODUCT CODE	SEO-25018-FORK
Viscosity Grade, SAE J300	10W
ISO Viscosity Grade	32
Density at 15°C, g/ml, ASTM D4052	0.870
Kinematic Viscosity at 40°C, mm²/s, ASTM D445	32
Kinematic Viscosity at 100°C, mm²/s, ASTM D445	6.29
Viscosity Index, ASTM D22700	150
Flash Point(COC), °C, ASTM D92	196
Pour Point, °C, ASTM D97	-39

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

/PDS/AL/070x- FO-10WCA-SHL/01*, 01.06.25, Page 1/1

* supersedes all previous versions

Packing : 700 ml ,800 ml , 1L , 2L, 3L, 4L, 5L, 6.5L, 7L, 8L,16L,18L, 20L, 25L, 200L, 205L, 208L, 210L